

## **Organic Peroxide Producers Safety Division**

The Society of the Plastics Industry, Inc. 1667 K. Street, NW, Suite 1000 Washington, DC 20006-1620

## **Liquid Organic Peroxide Spill Clean Up**

This guidance is intended for spills of 55 gallons or less. Review material safety data sheet with specific concerns related to the spilled material and for guidance regarding personal protective equipment.

Any organic peroxide spill should be attended to immediately to avoid the risks of chemical reactions which may result in fire or explosion, as well as the possible contamination of soil and/or water. Contact your organic peroxide supplier prior to acting, if there are any questions regarding safety issues. It is recommended that "spill kits" be available in all areas in which organic peroxide products are stored and used. The spill kit should be comprised of non-sparking clean-up tools, plastic garbage bags, closeable plastic containers, hazardous material labels, and a source of water.

Liquid spills can normally be handled by spreading an inert absorbent material such as sodium bicarbonate, or sand directly on the spill, then wetting down the mixture with water. Please note materials such as sawdust, peat moss and kitty litter (e.g. Oil-Dri ®) should not be used. The mixture of the spilled organic peroxide and the inert absorbent material should be swept up using non-sparking tools and placed in polyethylene bags for disposal. NOTE: A supply of suitable inert absorbent should be kept available for this purpose in areas where organic peroxides are used.

The sweepings in the polyethylene bag should be wetted down further, with water, and disposed of immediately by an approved disposal company. Please refer to www.OPPSD.org for links to disposal companies.

If stored for any period of time, the recovered materials should be out of direct sunlight in a cool, wellventilated location.

After all the material has been picked up, wash down the spill area with surfactant and water to remove any traces of organic peroxide. Allow for sufficient ventilation to aid in the removal of fumes that may be present

SPI/OPPSD makes no representation or warranties concerning the above information. This bulletin is being offered in an advisory capacity and is not to be used in lieu of any federal, state, local or quasi-public statute, regulation, ordinance or standard. Further, SPI makes no warranty, expressed or implied, regarding the use of any product.