

## Section 1: Product & Company Identification

Product Name: Copper Anti-Seize and Lubricating Compound

Product Number (s): SL35901, SL35903

Manufactured By: CRC Industries, Inc. 885 Louis Drive Warminster, PA 18974 www.crcindustries.com

 General Information
 (215) 674-4300

 Technical Assistance
 (800) 521-3168

 Customer Service
 (800) 272-4620

 24-Hr Emergency (CHEMTREC)
 (800) 424-9300

## Section 2: Hazards Identification

### **Emergency Overview**

Appearance & Odor: Copper semi-solid paste with petroleum odor

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

### **Potential Health Effects:**

EYE:	May cause irritation.
SKIN:	For hypersensitive persons, may irritate the skin after prolonged periods of time.
INHALATION:	Viscous nature may block breathing passages if inhaled.
INGESTION:	May cause diarrhea
CHRONIC EFFECTS:	None known
TARGET ORGANS:	None known

Medical Conditions Aggravated by Exposure:

pre-existing skin sensitivities

See Section 11 for toxicology and carcinogenicity information on product ingredients.

COMPONENT	CAS NUMBER	% by Wt.
Petroleum Oil	64742-57-0 / 64742-52-5	60 - 70
Nonhazardous blend	82980-54-9 / 471-34-1 / 14807-96-6	25 - 40
Graphite	7782-42-5	1 - 10
Copper powder	7440-50-8	1 - 10

## Section 3: Composition/Information on Ingredients

### Section 4: First Aid Measures

Eye Contact:	Immediately flush with plenty of water for 15 minutes or until all residual material is gone. Call a physician if irritation persists.
Skin Contact:	Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
Inhalation:	Remove person to fresh air. Keep person calm. Clear air passage. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
Ingestion:	Wash out mouth immediately. Consult physician.
Note to Physicians:	Treat symptomatically.

## Section 5: Fire-Fighting Measures

Flammable Properties:	This product is not flamm	able.	
Flash Point: Autoignition Temperature:	430 F (COC) > 500 F	Upper Explosive Limit: Lower Explosive Limit:	7.0 0.9
Suitable Extinguishing Media:	Foam, dry powder, Halon®, water jet.	carbon dioxide, sand, earth 8	k water mist. Do not use
Products of Combustion:	Smoke, soot, hydrocarbons	and oxides of carbon, sulfur &	& nitrogen.
Protection of Fire-Fighters:	protection against suffocation and skin protection should be	f-contained, NIOSH-approved on and possible toxic decompo be provided. Use water spray k down vapors which may res	osition products. Proper eye to keep fire-exposed

## Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Scrape up bulk, then wipe up remainder with cloth. To prevent walking hazard, pick up remaining residue with diatomaceous earth.

### Section 7: Handling and Storage

Handling Procedures: Do not use near sources of ignition. Provide adequate ventilation during use. Wear appropriate personal protective equipment.

Storage Procedures: Store in a cool dry area out of direct sunlight. Keep out of reach of children and pets.

Aerosol Storage Level: NA

### **Section 8: Exposure Controls/Personal Protection**

Exposure Guidelines:

	OSHA		AC	ACGIH OTHER			
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Petroleum oil	5*	NE	5*	NE	NE		mg/m <sup>3</sup>
Nonhazardous blend	NE	NE	NE	NE	NE		
Graphite	2.5 (v)	NE	2	NE	2.5	NIOSH	mg/m <sup>3</sup>
Copper powder	1	NE	0.1	NE	1	NIOSH	mg/m <sup>3</sup>
N.E. – Not Established	(c) – c	eiling (s	s) – skin	(v) – va	acated	* - oil mist	

Engineering Controls:	Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.
Respiratory Protection:	None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies.
Eye/face Protection:	For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.
Skin Protection:	Use protective gloves such as nitrile or PVC. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

### **Section 9: Physical and Chemical Properties**

Physical State: Semi-solid paste

## **Product Name:** Copper Anti-Seize and Lubricating Compound **Product Number (s):** SL35901, SL35903

Color: Copper/bronze		
Odor: Petroleum		
Specific Gravity: 1.09		
Initial Boiling Point: ND		
Freezing Point: ND		
Vapor Pressure: < 0.01 kPa		
Vapor Density: >5 (air = 1)		
Evaporation Rate: < 0.01 (butyl acetate = 1)		
Solubility: Negligible in water		
pH: NA		
Volatile Organic Compounds: <u>wt %</u> : 0	<u>g/L</u> : 0 <u>lbs./gal:</u> 0	

## Section 10: Stability and Reactivity

Stability:	Stable			
Conditions to Avoid: Sources of ig			gnition, temperature extremes	
Incompatible Materials: Strong inorganic and organic acids, oxidizing and copper reactive agents				
Hazardous Decomposition Products:		Products:	Smoke, airborne soot, hydrocarbons and oxides of carbon, sulfur, & nitrogen	
Possibility of Hazardous Reactions:		actions:	No	

## Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

## ACUTE EFFECTS

Component No information av		<u>est</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
CHRONIC EFFEC	TS				
Carcinogenicity:					
OSHA: IARC: NTP:	Component None listed None listed None listed		<u>Result</u>		
Mutagenicity:	No information	n available			
Other:	None				

## Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:

In extreme cases, may generate fractions that could act as a marine pollutant.

# **Product Name:** Copper Anti-Seize and Lubricating Compound **Product Number (s):** SL35901, SL35903

Persistence / Degradability:No information available.Bioaccumulation / Accumulation:Bioaccumulation potential nil.Mobility in Environment:Highly unlikely to cause widespread contamination.

## **Section 13: Disposal Considerations**

Disposal: This product is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33) Empty containers may be recycled.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

## **Section 14: Transport Information**

Proper shipping description:

US DOT (ground): Not Regulated

Special Provisions: None

## Section 15: Regulatory Information

### U.S. Federal

### Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: copper (5,000 lbs)

## Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

### Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	No
-	Reactive Hazard	No
	Release of Pressure	No
	Acute Health Hazard	Yes
	Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: Copper (< 10%)

### Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

### **State Regulations**

### California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: None

### State Right to Know:

New Jersey:	7440-50-8, 7782-42-5, 471-34-1
Pennsylvania:	7440-50-8, 7782-42-5, 471-34-1
Massachusetts:	7440-50-8, 7782-42-5, 471-34-1
Rhode Island :	7440-50-8, 7782-42-5, 471-34-1

Additional Regulatory Information: None

### Section 16: Other Information

NFPA:	Health:	1	Flammability:	1	Reactivity:	1		
HMIS:	Health:	1	Flammability:	1	Reactivity:	1	PPE:	В

Prepared By:	Michelle Rudnick
CRC #:	SL35901
Revision Date:	09/09/2008

Changes since last revision: Part number removed

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
PMCC:	Pensky-Martens Closed Cup	g/L:	grams per Liter
PPE:	Personal Protection Equipment	lbs./gal:	pounds per gallon
TWA:	Time Weighted Average	STEL:	Short Term Exposure Limit
OSHA:	Occupational Safety and Health Administration		
ACGIH	American Conference of Governmental Industrial Hygienists		
NIOSH	National Institute of Occupational Safety & Health		