



Global Marine Products

Material Safety Data Sheet

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

DISTILLATE MARINE GAS OIL (DMA)

Product Use: Gas Oil

Product Number(s): 32782

Synonyms: MARINE GAS OIL - 1% SULPHUR

Company Identification

Chevron Products UK Limited

1 Westferry Circus

Canary Wharf

London E14 4HA

United Kingdom

+44(0)20 77 19 3000

Transportation Emergency Response

Europe: 0044/(0)18 65 407333

Health Emergency

Chevron Emergency Information Center: Emergency Information Centers are located in the USA.

International collect calls accepted. (800) 231-0623 or (510) 231-0623

Product Information

Product Information: +44(0)20 77 19 3000

FAX number: +44(0)20 77 19 5171

SECTION 2 COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENTS	EC NUMBER	SYMBOL / RISK PHRASES	AMOUNT
Fuels, diesel; Gasoil - unspecified	269-822-7	Xn/Carc. Cat. 3/R40, Xn/R65, R66, N/R51/53	100 %weight

The full text of all R-phrases is shown in Section 16.

SECTION 3 HAZARDS IDENTIFICATION

CLASSIFICATION: Carc. Cat. 3; R40 | Xn; R65 | R66 | N; R51/53 |

IMMEDIATE HEALTH EFFECTS

Eye: Not expected to cause prolonged or significant eye irritation.

Skin: Skin contact may cause drying or defatting of the skin. Symptoms may include pain, itching, discoloration, swelling, and blistering.

Ingestion: Because of its low viscosity, this material can directly enter the lungs, if swallowed, or if subsequently vomited. Once in the lungs it is very difficult to remove and can cause severe injury or death.

Inhalation: Not expected to be harmful if inhaled.

DELAYED OR OTHER HEALTH EFFECTS: Prolonged or repeated exposure to this material may

cause cancer.

ENVIRONMENTAL EFFECTS: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 4 FIRST AID MEASURES

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

Skin: Wash skin with water immediately and remove contaminated clothing and shoes. Get medical attention if any symptoms develop. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: If swallowed, get immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

Note to Physicians: Ingestion of this product or subsequent vomiting may result in aspiration of light hydrocarbon liquid, which may cause pneumonitis.

SECTION 5 FIRE FIGHTING MEASURES

See Section 7 for proper handling and storage.

FLAMMABLE PROPERTIES:

Flashpoint: (Pensky-Martens Closed Cup) 61.5 °C (143 °F) Minimum

Autoignition: 350 °C (662 °F)

Flammability (Explosive) Limits (% by volume in air): Lower: 1 Upper: 6

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

PROTECTION OF FIRE FIGHTERS:

Fire Fighting Instructions: This material will burn although it is not easily ignited. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures: Eliminate all sources of ignition in vicinity of spilled material.

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Reporting: Report spills to local authorities as appropriate or required.

SECTION 7 HANDLING AND STORAGE

Specific Use: Gas Oil

Precautionary Measures: Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Do not

breathe vapor or fumes. Do not breathe mist. Wash thoroughly after handling.

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 3), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

ENGINEERING CONTROLS:

Use in a well-ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

Skin Protection: Wear protective clothing to prevent skin contact. Selection of protective clothing may include gloves, apron, boots, and complete facial protection depending on operations conducted. Suggested materials for protective gloves include: Chlorinated Polyethylene (or Chlorosulfonated Polyethylene), Nitrile Rubber, Polyurethane, Viton.

Respiratory Protection: If exposure to harmful levels of airborne material may occur when working with this material, wear an approved respirator that provides protection, such as: No respiratory protection is normally required. Air-Purifying Respirator for Organic Vapors.

Occupational Exposure Limits:

Component	Country/ Agency	TWA	STEL	Ceiling	Notation
Fuels, diesel; Gasoil - unspecified	CVX	--	1000 mg/m3	--	--

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

Color: Amber

Physical State: Liquid

Odor: Petroleum odor

pH: Not Applicable

Vapor Pressure: 0.04 kPa (Approximate) @ 40 °C (104 °F)

Vapor Density (Air = 1): >1
Boiling Point: 160°C (320°F) - 400°C (752°F)
Solubility: Insoluble
Freezing Point: Not Applicable
Density: 810 - 890 kg/m³ @ 15°C (59°F)
Viscosity: 1.5mm²/s @ 40°C (104°F) Minimum

SECTION 10 STABILITY AND REACTIVITY

Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Conditions to Avoid: Avoid contact with heat, sparks, fire and oxidizing agents

Incompatibility With Other Materials: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous Polymerization: Hazardous polymerization will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

IMMEDIATE HEALTH EFFECTS

Eye Irritation: The Draize eye irritation mean score in rabbits for a 24-hour exposure was: <10/110.

Skin Irritation: For a 24-hour exposure, the Primary Irritation Score (PIS) in rabbits is: >5 / 8.0.

Skin Sensitization: This material did not cause skin sensitization reactions in a Buehler guinea pig test.

Acute Dermal Toxicity: LD50: >5ml/kg (rabbit).

Acute Oral Toxicity: LD50: >5 ml/kg (rat)

Acute Inhalation Toxicity: 4 hour(s) LC50: >5mg/kg (rat).

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY

This material is expected to be toxic to aquatic organisms.

48 hour(s) Water Accomodated Fraction: 20-210 mg/l (Daphnia magna)

72 hour(s) Water Accomodated Fraction: 2.6-25 mg/l (Raphidocellus subcapitata)

96 hour(s) Water Accomodated Fraction: 21-210 mg/l (Salmo gairdneri)

MOBILITY

No data available.

PERSISTENCE AND DEGRADABILITY

May cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from products of a similar structure and composition.

POTENTIAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.

Octanol/Water Partition Coefficient: No Data Available

SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by international, country, or local laws and regulations. In accordance with European Waste Catalogue (E.W.C.) the codification is the following: 13 07 01

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

ADR/RID Shipping Description: UN1202 GAS OIL, 3, III, ADR CODE F1 , Hazard ID No.30

ICAO/IATA Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORTATION UNDER ICAO

IMO/IMDG Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORTATION UNDER THE IMDG CODE

SECTION 15 REGULATORY INFORMATION

REGULATORY LISTS SEARCHED:

01=EU. Directive 76/769/EEC: Restrictions on the marketing and use of certain dangerous substances.

02=EU Directive 90/394/EEC: Carcinogens at work.

03=EU Directive 92/85/EEC: Pregnant or breastfeeding workers.

04=EU Directive 96/82/EC (Seveso II): Article 9.

05=EU Directive 96/82/EC (Seveso II): Articles 6 and 7.

06=EU Directive 98/24/EC: Chemical agents at work.

The following components of this material are found on the regulatory lists indicated.

Fuels, diesel; Gasoil - unspecified 03, 06

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), IECSC (China), KECI (Korea), PICCS (Philippines), TSCA (United States).

CLASSIFICATION - LABELING:

Under the criteria of the directive EEC/67/548 (dangerous substances) and EEC/1999/45 (dangerous preparations):

- contains: Fuels, diesel; Gasoil - unspecified

Symbols: Xn - Harmful

N - Dangerous for the environment

R40; Limited evidence of a carcinogenic effect.

R65; Harmful: may cause lung damage if swallowed.

R66; Repeated exposure may cause skin dryness or cracking.

R51/53; Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S36/37; Wear suitable protective clothing and gloves.

S61; Avoid release to the environment. Refer to special instructions/safety data sheets.

S62; If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

SECTION 16 OTHER INFORMATION

REVISION STATEMENT: This revision updates the following sections of this Material Safety Data Sheet: 5,9,13

Revision Date: MARCH 06, 2007

Full text of R-phrases:

R40; Limited evidence of a carcinogenic effect.

R51/53; Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65; Harmful: may cause lung damage if swallowed.

R66; Repeated exposure may cause skin dryness or cracking.

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
CVX - Chevron	CAS - Chemical Abstract Service Number

Prepared according to the criteria of the directive 2001/58/EC by the Chevron Energy Technology Company, 100 Chevron Way, Richmond, California 94802.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.