

Job Safety Analysis Form

Picture of task/equipment:	Task:	Circular saws
	Name of Shop or Dept:	OCH Maintenance, UA, LACC
	Job Title(s):	Building Maintenance, Carpenter
	Analyzed by:	M. Williams
	Date:	04/30/13
Required PPE:		
Work boots	hearing protection	safety glasses dust mask
Required/Recommended Trainings:		
STF Safety	Machine Guardir	ng Equipment safety precautions
TASK	HAZARDS	CONTROLS
Operating a Circular Saw power tool	Laceration Amputation Struck By Puncture Slip Trip Fall Fire	Con PPE, including safety glasses, work boots (non- slip soles), Hearing protection and a dust mask when saw dust is present. Keep loose clothing, hair and jewelry away from moving parts to prevent getting caught in blade. Keep hands away from cutting area and blade. Second hand should be placed on handle or over motor to ensure no free hands can come in contact with the blade. Before beginning to cut, adjust blade depth to just past the piece you will be cutting. Never remove the guard. Never attempt to reach under the blade to remove a work piece. Never hold piece to be cut with your hand or across your leg. Instead secure to a stable surface with a clamp or vice grips if small. Never use damaged or incorrect blades, washers or bolts. This can cause injury from flying debris. Never attempt to pull the saw blade out of the work

while the blade is still spinning. Ensure it comes to a

When restarting the saw, make sure the teeth are not in contact with the work piece. This can create the

Keep blade aligned with work piece to prevent pinching, binding or twisting this will result in kick back.

complete rest before removing from work.

blade to "walk up" or kick back.